



Fire sleeve - F88 SC · Model KV

Silicone-coated fire sleeve with Velcro fastener for subsequent assembly.

Certifications DIN EN 45545-2:2020 R22/R23-HL3

Technical data

Source material	Fire sleeve F88 SC
Fastening	Velcro fastener flame retardant, DIN 75200 / ISO 3795
Technical values	Velcro fastener width to DN90 = 30 mm; from DN100 = 38 mm Kevlar® strips type KV290 as edge protection
Available sizes	Available lengths on demand, maximum 25 m not a stock item; delivery time after consultation

Key characteristics

- excellent mechanical protection
- halogen-free flame protection
- free of softeners
- free of heavy metals
- REACH-compliant
- Puncture strength DIN EN 60684 >10kv

Product details

DN	product number	approx. weight g/m	DN	product number	approx. weight g/m
30	4499 8 030	520	130	4499 8 130	1550
40	4499 8 040	615	140	4499 8 140	1630
50	4499 8 050	715	150	4499 8 150	1750
60	4499 8 060	810	160	4499 8 160	1850
70	4499 8 070	930	170	4499 8 170	1945
80	4499 8 080	1040	180	4499 8 180	2045
90	4499 8 090	1135	190	4499 8 190	2160
100	4499 8 100	1230	200	4499 8 200	2270
110	4499 8 110	1330	220	4499 8 220	2460
120	4499 8 120	1440	250	4499 8 250	2755

