



Fire sleeve - F 88 PYC

The flat coated fire sleeve with polychloroprene and high material density.

Certifications

DIN 5510-2:1999 + ISO 5659 Toxi
ISO 15540:1999 NW20
Type Approval GL (Germanischer Lloyd)

Technical data

Backing material ISO 2078 mineral fibre
Coating PYC

Technical values Temperature range: -40 to +260 °C; Maximum temperature (short-term): +800 °C
Thickness: 2.5 - 3.0 mm; Weight: 2.8 kg/m²; REACH: complies

Available sizes DN14 – DN140; Available lengths 25 m; 50 m on request

Product details

DN	Product number	approx. weight g/m	DN	Product number	approx. weight g/m
14	4418 8 014	212	50	4418 8 050	442
16	4418 8 016	215	52	4418 8 052	453
18	4418 8 018	234	55	4418 8 055	464
20	4418 8 020	245	60	4418 8 060	488
22	4418 8 022	256	65	4418 8 065	578
24	4418 8 024	266	70	4418 8 070	630
26	4418 8 026	278	75	4418 8 075	650
28	4418 8 028	290	80	4418 8 080	684
30	4418 8 030	301	85	4418 8 085	755
32	4418 8 032	314	90	4418 8 090	800
36	4418 8 036	328	100	4418 8 100	860
38	4418 8 038	340	110	4418 8 110	890
40	4418 8 040	353	120	4418 8 120	920
42	4418 8 042	371	125	4418 8 125	978
45	4418 8 045	387	140	4418 8 140	983
48	4418 8 048	408			