



Fire sleeve - F 88 SC Flex

The extruded and flexible fire sleeve with silicone coating for easy installation.

Certifications DIN 5510-2:2009 + ISO5659 Toxi

Technical data

Backing material ISO 2078 mineral fibre
Coating Silicone - ISO 1629 MVQ/VMQ

Technical values Temperature range: -60°C to +450°C
 Maximum temperature (short-term): +1.100°C
 Thickness: 3.0 - 3.5 mm,
 Weight: 4.5 kg/m²
 REACH: complies

Available sizes DN5 – DN47
 Available lengths 25 m; 50 m on request

Product details

DN	Product number	approx. weight g/m	DN	Product number	approx. weight g/m
30	4499 9 030	580	130	4499 9 130	1610
40	4499 9 040	675	140	4499 9 140	1690
50	4499 9 050	775	150	4499 9 150	1810
60	4499 9 060	870	160	4499 9 160	1910
70	4499 9 070	990	170	4499 9 170	2005
80	4499 9 080	1100	180	4499 9 180	2105
90	4499 9 090	1195	190	4499 9 190	2220
100	4499 9 100	1290	200	4499 9 200	2330
110	4499 9 110	1390	220	4499 9 220	2520
120	4499 9 120	1500	250	4499 9 250	2815