



Fire sleeve - F 88 VIGOSIL

The cost-effective, round-dipped fire sleeve with silicone coating.

Certifications DIN EN 45545-2:2016-R22/R23-HL3
 (DIN EN 45545-2:2013-08+A1:2015)
 ISO 15540:1999 NW20)

Technical data

Backing material ISO 2078 mineral fibre, Woven fabric up to DN40, knitted fabric up to DN110
Coating Silicone - ISO 1629/LSR

Technical values Temperature range: -60°C to +450°C
 Maximum temperature (short-term): +1.100°C
 Thickness: 3.0 - 4.0 mm
 Weight: 4.5 kg/m²
 REACH: complies

Available sizes DN6 – DN110; available lengths 40 m up to DN40, 25 m up to DN110

Product details

DN	Product number	approx. weight g/m	DN	Product number	approx. weight g/m
6	4448 8 006	204	40	4448 8 040	461
8	4448 8 008	228	44	4448 8 044	492
10	4448 8 010	249	50	4448 8 050	438
13	4448 8 013	262	57	4448 8 057	581
15	4448 8 015	281	60	4448 8 060	610
20	4448 8 020	304	65	4448 8 065	740
22	4448 8 022	321	70	4448 8 070	800
25	4448 8 025	342	75	4448 8 075	895
30	4448 8 030	394	80	4448 8 080	1215
32	4448 8 032	416	90	4448 8 090	1367
35	4448 8 035	436	100	4448 8 100	1418
38	4448 8 038	450	110	4448 8 110	1588