



Screw fittings for fire sleeve F 88 SC and F 88 SC Flex

Hose systems are an important installation and organisation criteria for bundling individual cables. The use of fire sleeves makes this system flame-resistant according to existing standards and guarantees a high retention of function in the event of a fire. The fittings are absolutely watertight in the force-fit connection to the hose. We assemble the required hose line after provision of the cables, which we are also happy to do in our own workshop if you so require.

Technical data

Connections metric thread according to EN 60423 or PG DIN 40430

Product details · F 88 SC

DN	thread EN 60423	product number fitting	smallest internal diameter mm	SW 1 · SW 2 mm	for F 88 SC product number
10	M 16 x 1,5	44405 3 410	11,5	23/25	4488 8 010
15	M 20 x 1,5	44405 3 415	16,0	27/29	4488 8 015
20	M 25 x 1,5	44405 3 420	21,0	34/36	4488 8 020
30	M 32 x 1,5	44405 3 425	27,5	43/45	4488 8 030
40	M 40 x 1,5	44405 3 440	35,0	52/54	4488 8 040
50	M 50 x 1,5	44405 3 450	45,0	63/66	4488 8 050

Product details · F 88 SC Flex

DN	thread EN 60423	product number fitting	smallest internal diameter mm	SW 1 · SW 2 mm	for F 88 SC product number
10	M 16 x 1,5	44405 3 410	11,5	23/25	4488 8 010
15	M 20 x 1,5	44405 3 415	16,0	27/29	4488 8 015
20	M 25 x 1,5	44405 3 420	21,0	34/36	4488 8 020
30	M 32 x 1,5	44405 3 425	27,5	43/45	4488 8 030
40	M 40 x 1,5	44405 3 440	35,0	52/54	4488 8 040
50	M 50 x 1,5	44405 3 450	45,0	63/66	4488 8 050

Tolerances of the coating thickness may cause increased assembly expenditure.